Single-color LED Strip (9.6W/M)

Datasheet



L2080

Please scan the QR code above to check the latest version of datasheet!

Before using this product, please read this datasheet carefully and keep it properly!

Document Version：C

◇◆ Overview

Single-color LED Strip (9.6W/M) is an ultra-thin, high-efficiency LED strip that utilizes energy-saving enhanced 2835 LEDs with an asymmetric light distribution profile. It features a pre-applied high-performance 3M double-sided tape on the back for quick and secure installation. Specifically engineered for precise wall grazing, it beautifully accentuates the contours and layered details of curved surfaces. Ideal for both indoor and outdoor applications, it is widely used in residential, commercial, and hospitality settings such as homes, luxury residences, clubs, shopping malls, retail stores, and hotels.

Note: In practical applications, the power supply should have a 20% margin (it is recommended to only use 80% of the power) to ensure sufficient voltage to drive the product.

Main Functions:

- Asymmetric lighting and Side bending
- 2835 side lighting LED inside
- Diffused silicone extrusion
- UV and yellowish resistant
- IP66 and salt-mist proof
- L70B50 > 50,000hrs
- Easy installation and re-connect accessories
- 576lm per meter @4000K
- ~9.6W/mtr, continuous length 10mtrs
- Bending radius 5cm

◇◆ Appearance



Figure 1

◇◆ Technical Data

Item	Parameter
Input voltage	DC24V
Driving mode	Constant Voltage

Power/m	9.6W/m
Lm/m	576lm@4000K
CRI	≥90Ra
Beam angle	120°
Available color	2700K/3000K/3500K/4000K/5000K/Red/Green/Blue
Max. length (Single-end power feeding)	10m
Cutting unit	50mm
LED Qty/m	120LEDs/m

◇◆ Specifications

Item	Parameter
Dimensions(L*W)	50mm x 8mm
Installation	Pasting

◇◆ Safety Precaution

Danger:

- Please do not privately disassemble or replace any parts of the product. Otherwise, it may cause mechanical fault, electric shock, fire or personal injuries.
- Under no circumstances should the product be covered by insulation pads or similar materials.

Warning:

- The installation and testing for the product must be carried out by HDL Automation Co., Ltd. (hereinafter referred to as HDL) or its appointed service agencies. The electric construction shall comply with local laws and safety regulations.
- HDL will not be responsible for any consequence caused by the inexpert or faulty installation and wiring methods, which are not in accordance with the instructions contained in this datasheet.
- Please contact HDL after-sales departments or our designated service agencies for your maintenance service. Product failures caused by private disassembly are not subject to the warranty.

Caution:

- Before performing any installation or disassembly procedures on the device, it is crucial to disconnect the device from all

voltage sources. This step is necessary to ensure the safety of the technician and prevent any potential damage to the device.

- Do not use corrosive liquid to wipe the device body, especially the interface, so to avoid damage to the device. Do not wipe the device with a damp cloth.
- Before performing any maintenance or cleaning procedures on the device, it is imperative to disconnect the device from all voltage sources. This precautionary measure is necessary in order to prevent electric leakage and the risk of electric shock.
- After all of the cables are terminated, check for correct and good terminations.
- Overrange is not allowed. Please use the device in accordance with the technical specifications.

Note:

- Please use a 24V DC isolated power supply to drive LED light strips, and the ripple of the constant voltage source should be less than 5%. Resistive capacitive voltage reduction, non isolated, and other types of power supplies should not be used to drive LED light strips.
- To ensure the lifespan and reliability of the light strip, please do not bend it in an arc with a diameter of less than 60mm, and do not fold it in half to avoid damaging or breaking the light beads.
- To ensure the lifespan and usage environment of the LED strip, do not forcefully pull or tug on the power cord during use, and do not collide to avoid damaging the LED light.
- During installation, pay attention to the correct wiring of positive and negative poles of the power cord, and ensure that the voltage of the power supply is consistent with that of the product to avoid product damage.
- LED light strips should be stored in a dry and sealed environment. It is recommended that the storage period should not be too long. Please open the seal before use. The working environment temperature is -20 ℃~45 ℃, and the storage temperature is 0 °C~60 ℃. Non waterproof light strips should be used indoors, and the relative humidity should not exceed 70%.
- Please be careful during operation and do not touch the AC power end when the power is connected to prevent electric shock.
- In practical applications, the power supply should have a 20% margin (it is recommended to only use 80% of the power) to ensure sufficient voltage to drive the product.
- It is strictly prohibited to use any acidic or alkaline adhesives to fix products (including but not limited to glass glue, etc.).

◇◆ Installation

Warning:

- Before performing any installation or disassembly procedures on the device, it is crucial to disconnect the device from all voltage sources. This step is necessary to ensure the safety of the technician and prevent any potential damage to the

device.

- Connect the wires according to the positive and negative leads of the LED driver, and do not connect them in reverse.

Installation: Please apply 3M tape to the back of the light strip and attach it to the desired location.

◇◆ Disassembly

Warning: Before disassembling, please cut off the power supply, and operation with electricity is prohibited.

◇◆ Packing List

- LED Strip*1

Note: After unpacking, please check if the product and the parts are complete.

◇◆ Copyright Statement

HDL has all the intellectual property rights to this document and contents thereof. Reproduction or distribution for third parties are prohibited without written authorization from HDL. Any infringement of HDL’s intellectual property rights will be investigated the legal liability.
The contents of this document will be updated as the updates of product versions or other reasons. Unless otherwise agreed upon, this document is to be used as a guidance only. All the statements, information and recommendations in this document makes no warranty expressed or implied.
© 2025 HDL Automation Co., Ltd. All rights reserved.

Update History:

The form below contains the information of every update. The latest version contains all the updates of all former versions.

Version	Update Information	Date
V1.0	Initial release	Sept 25, 2025

◇◆ Technical Support

E-mail: hdltickets@hdlautomation.com

Website: https://www.hdlautomation.com